

Yaylı Tip Sigortalı ve Baralı Klemensler

Spring Clamp Fuse and Disconnect Terminals

Klemensler, Ø5x20 veya Ø5x25 cam sigorta takılabilen ve yedek sigorta yuvası bulunan bir kartuşa sahiptir. Ayırma klemensleri ise bağlı buldukları akım devrelerinde üzerlerinde bulunan ayırma mandalı sayesinde iletkenleri yerinden sökmeden devreyi açmaya ve kapamaya yararlar. İstenildiği takdirde ayırma mandalı içindeki bara uygun bir sigortayla değiştirilerek sigortalı klemens olarak da kullanılabilir.

The terminal has a moving type hinged carrier that has a specially designed space for cartridge type glass fuse of size Ø5x20 or Ø5x25 together with a spare one. Disconnect Terminals can switch the circuit without disconnecting the conductors by a disconnect busbar, in the disconnect, the disconnect busbar can be changed with a proper fuse to use as a fuse terminal optionally.




Anma Değerleri / Electrical Ratings

TSE / CE (EN 60947-7-1 / 60947-7-2)
UL / CSA

Kablo Soyma Boyu / Insulation Stripping Length

YBK S

Kalınlık/Width 8 mm
355 119
GRI / GREY



Bağlantı Bilgileri / Connection Data

Tekli İletken, Yay Baskılı / Solid Strand, Clamp Connection

Çoklu İletken, Yay Baskılı / Fine Strand, Clamp Connection

AWG İletken / AWG Conductor

Sipariş Bilgileri / Ordering Data

Polyamide 6.6

BEJ - BEIGE / GRI - GREY
BEJ - BEIGE / GRI - GREY
BEJ - BEIGE / GRI - GREY
BEJ - BEIGE / GRI - GREY
BEJ - BEIGE / GRI - GREY
BEJ - BEIGE / GRI - GREY
BEJ - BEIGE / GRI - GREY
BEJ - BEIGE / GRI - GREY

Genilim / Akım / Kesit / Voltage/Current/Cross-section

500 V - / 10 A / 4 mm²
600 V - / 10 A / AWG 22-10

12 mm

0,5 6 mm²

0,5 4 mm²

22 10

Tip/Type

Sip.No./Cat.No.

Mik./Qty.

YBK S


355 110 / 355 119

20

Montaj Rayları / Mounting Rails

MR 35x7.5
MR 35x7.5 Delikli / Slotted

MR 35x15
MR 35x15 Delikli / Slotted



DIN EN 50022

DIN EN 50022

Tip/Type

Sip.No./Cat.No.

Mik./Qty.

MR 35x7.5

500 601

1 m

Delikli / Slotted

500 602

1 m

MR 35x7.5

500 603

2 m

Delikli / Slotted

500 604

2 m

MR 35x7.5

500 605

30 cm

MR 35x15

500 606

1 m

Delikli / Slotted

500 607

1 m

Durdurucu / End Bracket

Kalınlık / Thickness 8 mm



KD 3

KD 4

GRI / GREY

GRI / GREY

Tip/Type

Sip.No./Cat.No.

Mik./Qty.

KD 3

495 049

100

KD 4

495 059

100

Nihayet Plakası / End Plate

Polyamide 6.6

Kalınlık / Thickness 1.5 mm.

BEJ / BEIGE

GRI / GREY



NPP YBK S - YBK I

NPP YBK 2.5 A

Tip/Type

Sip.No./Cat.No.

Mik./Qty.

NPP YBK S - YBK I

450 060

10

NPP YBK S - YBK I

450 069

10

Üst Köprü / Cross - Connection



Tip/Type

Sip.No./Cat.No.

Mik./Qty.

UK 6/2

476 242

25

UK 6/3

476 243

20

UK 6/4

476 244

15

UK 6/10

476 249

5

Sigorta Buşonu / Fuse Cartridges



5 x 20 mm.

5 x 25 mm.

1 10 A

1 10 A

Tip/Type

Sip.No./Cat.No.

Mik./Qty.

MSB

359 001

10

MSB

359 002

10

Grup Etiketleri / Group Marking



GRI / GREY

GRI / GREY

Tip/Type

Sip.No./Cat.No.

Mik./Qty.

GE

496 119

50

ME

496 139

25

Klemens Etiketleri / Marking Tags (Dekafix)

Dekafix kullanımı için 62. sayfaya bakınız.

See page 62. for the usage of dekafix.

Tip/Type

DY 5